



GAS FLATWORK DRYER-IRONER Ø 500X2600MM GC 2650 G

Ref: 0913.12.028 Grandimpianti

Structure in painted sheet and plastic coated sheet metal.

Easy to use 7 2 touch screen with 37 languages available.

Front-service type to be used by one or two operators. The rotary drying press can be installed against a wall.

Roller ironing speed adjustable between 1m/min. and 8m/min. thanks to the motor controlled with inverter technology.

Finger-saving fillet protects the operator in case of mishandling.

Manual device to move the roller and remove the washing in case of power failure.

Electronic device controls start and gas flame.

Steam version, on request.

- * with length folder or pass through (optional).
- ** with length folder (optional).
- *** with length folder and pass through (optional).

FEATURES	
Dimensions (WDH)	3445x1070(*1417)x1420 mm
Power supply	400V/3/50 Hz
Motor power	0.87 kW (**+0.56 kW/***+0.74 kW)
Capacity	60 - 80 kg/h
Roller	Ø 500x2600 mm
Speed roller	1 - 8 m/min
Extraction power	2x 600 m3/h
Flue outlet	2x Ø 153 mm
Gas thermal power	55 kW
Natural gas consumption	5.8 m3/h

GPL gas consumption 4.3 kg/h

Total electric power 0.87 kW (**+0.56 kW /***+0.74 kW)