


AUTOMATIC ROLLER IRONER WITH ROLLER SPEED CONTROL + VACUUM + NOMEX FABRIC AND MAXPRESS COATING, Ø 300X1600 MM S-160/30 AVL - VAPOR

Ref: 0912.12.024
 Grandimpianti



Specially-processed aluminum basin that ensures long life and energy conservation.
 Roller supported by bearings.
 Front loader use: The ironer can be installed against a wall.
 Finger safety band protects the user in case of mismanouver.
 Electronic control unit that monitor all machine running parameters and optimizes performance and energy consumption.
 Safety thermostat avoids undesirable overheating.
 Wide pedal for press movement control.
 Manual device for lifting the basin in power down events.
 Automatic press operation.

FEATURES

Dimensions (WDH)	2200x500x1100 mm
Total power	0.48 kW
Steam heating	10 - 12 bar
Power supply	400V/3/50 Hz
Capacity (H.R. 10-15%); (H.R. 20-25%); (H.R. 40-45%)	25/30 kg/h , 26/37 kg/h , 20/25 kg/h
Roller	Ø 300x1600 mm
Speed roller	2 - 4 m/min
Air consumption	200 m3/h
Steam consumption	35 kg/h
Flue outlet	55 mm
Net weight	262 kg