



## HIGH SPIN WASHING MACHINE, 18 KG GWH 180E

Ref: 0903.12.035 Grandimpianti

Electronic control Wavy®: user interface adaptable to user needs and skills; unlimited possibility to create and customize programs. Possibility to record all working data.

Drum speed electronically managed (inverter), with control of drum rotation by sensor.

Redundant securities tested by certified laboratory.

Machine frame projected to fix the machine without moving it.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached .

Patented weighing system to automatically weight the linen and regulate accordingly consumptions.

3 water inlets standard featured: hot, hard cold, soft cold, automatically managed and mixed by Wavy®.

Discharge pipe 3<sup>[7]</sup>? with 90° bend and 3 water loading pipes <sup>3</sup>/<sub>4</sub> Standard featured (Hot water, cold water, soft water).

Self-Service program, as standard.

Optional: Payment system - Electromechanical coin meter, electronic coin meter and central payment system.

Ready for 13 liquid detergent inlets (optional), dispenser with 4 compartments ergonomically placed as standard.

Control card for 1 pump 24Vac or 24Vrac (A104).

Optional A103/A108 also controls the detergent consumption.

The data are related to the 60° C wash cycle reported on the standard ISO 9398

Capacity drum         180 I - Ø 730x450 mm           Door         Ø 460 mm           Spin R.P.M         20 - 60 / 970           Spin G Factor         400           Noise         <65 dB           Dimensions (WDH)         970x1000x1460 mm           Weight net         385 kg           Weight gross         400 kg           Heating power - supplied with hot water only         Yes           Heating power - electric standard         18 kW           Motor - power         3.36 kW           Power supply - standard         380 - 415 V 3 N ~ 50/60 Hz           Consumption - hot water         38.5 I           Consumption - warm water         38.5 I           Consumption - cold water         77 I           Consumption - cycle length         56 min           Consumption - cycle length         56 min           Control - Wavy         Yes           Electric water drain         3[2]           Chemical supply - soap hopper         Yes           Chemical supply - ready for liquid soap supply         Yes           Packaging dimensions         1066x1070x1610 mm           Gross weight         390 kg	Capacity Load, min max. (1:10 / 1:9)	9 - 18 kg / 10 - 20 kg
Spin R.P.M         20 - 60 / 970           Spin G Factor         400           Noise         <65 dB	Capacity drum	180 I - Ø 730x450 mm
Spin G Factor         400           Noise         <65 dB	Door	Ø 460 mm
Noise < 65 dB  Dimensions (WDH) 970x1000x1460 mm  Weight net 385 kg  Weight gross 400 kg  Heating power - supplied with hot water only Yes  Heating power - electric standard 18 kW  Motor - electronic control Yes  Motor - power 3.36 kW  Power supply - standard 380 - 415 V 3 N ~ 50/60 Hz  Consumption - hot water 38.5 I  Consumption - cold water 77 I  Consumption - electric energy 5.168 kW/h  Consumption - cycle length 56 min  Control - Wavy Yes  Electric water drain 3121  Chemical supply - ready for liquid soap supply Yes  Chemical supply - ready for liquid soap supply  Packaging dimensions 1065x1070x1610 mm	Spin R.P.M	20 - 60 / 970
Dimensions (WDH)  Weight net  385 kg  Weight gross  400 kg  Heating power - supplied with hot water only  Yes  Heating power - electric standard  18 kW  Motor - electronic control  Yes  Motor - power  3.36 kW  Power supply - standard  380 - 415 V 3 N - 50/60 Hz  Consumption - hot water  38.5 I  Consumption - warm water  38.5 I  Consumption - cold water  77 I  Consumption - electric energy  5.168 kW/h  Consumption - cycle length  56 min  Control - Wavy  Yes  Electric water drain  3[2]  Chemical supply - ready for liquid soap supply  Yes  Packaging dimensions  1065x1070x1610 mm	Spin G Factor	400
Weight net  Weight gross  400 kg  Heating power - supplied with hot water only  Yes  Heating power - electric standard  18 kW  Motor - electronic control  Yes  Motor - power  3.36 kW  Power supply - standard  380 - 415 V 3 N - 50/60 Hz  Consumption - hot water  38.5 I  Consumption - warm water  38.5 I  Consumption - cold water  77 I  Consumption - electric energy  5.168 kW/h  Consumption - cycle length  56 min  Control - Wavy  Yes  Electric water drain  3[2]  Chemical supply - ready for liquid soap supply  Yes  Packaging dimensions  1065x1070x1610 mm	Noise	<65 dB
Weight gross     400 kg       Heating power - supplied with hot water only     Yes       Heating power - electric standard     18 kW       Motor - electronic control     Yes       Motor - power     3.36 kW       Power supply - standard     380 - 415 V 3 N ~ 50/60 Hz       Consumption - hot water     38.5 I       Consumption - warm water     38.5 I       Consumption - cold water     77 I       Consumption - electric energy     5.168 kW/h       Consumption - cycle length     56 min       Control - Wavy     Yes       Electric water drain     32       Chemical supply - soap hopper     Yes       Chemical supply - ready for liquid soap supply     Yes       Packaging dimensions     1065x1070x1610 mm	Dimensions (WDH)	970x1000x1460 mm
Heating power - supplied with hot water only  Heating power - electric standard  18 kW  Motor - electronic control  Yes  Motor - power  3.36 kW  Power supply - standard  380 - 415 V 3 N ~ 50/60 Hz  Consumption - hot water  38.5 I  Consumption - warm water  38.5 I  Consumption - cold water  77 I  Consumption - electric energy  5.168 kW/h  Consumption - cycle length  56 min  Control - Wavy  Yes  Electric water drain  3[2]  Chemical supply - soap hopper  Yes  Chemical supply - ready for liquid soap supply  Packaging dimensions  1065x1070x1610 mm	Weight net	385 kg
Heating power - electric standard  Motor - electronic control  Yes  Motor - power  3.36 kW  Power supply - standard  380 - 415 V 3 N ~ 50/60 Hz  Consumption - hot water  38.5 I  Consumption - warm water  38.5 I  Consumption - cold water  77 I  Consumption - electric energy  5.168 kW/h  Consumption - cycle length  56 min  Control - Wavy  Yes  Electric water drain  3	Weight gross	400 kg
Motor - electronic controlYesMotor - power3.36 kWPower supply - standard380 - 415 V 3 N ~ 50/60 HzConsumption - hot water38.5 IConsumption - warm water38.5 IConsumption - cold water77 IConsumption - electric energy5.168 kW/hConsumption - cycle length56 minControl - WavyYesElectric water drain3☑Chemical supply - soap hopperYesChemical supply - ready for liquid soap supplyYesPackaging dimensions1065x1070x1610 mm	Heating power - supplied with hot water only	Yes
Motor - power3.36 kWPower supply - standard380 - 415 V 3 N ~ 50/60 HzConsumption - hot water38.5 IConsumption - warm water38.5 IConsumption - cold water77 IConsumption - electric energy5.168 kW/hConsumption - cycle length56 minControl - WavyYesElectric water drain3[2]Chemical supply - soap hopperYesChemical supply - ready for liquid soap supplyYesPackaging dimensions1065x1070x1610 mm	Heating power - electric standard	18 kW
Power supply - standard  380 - 415 V 3 N ~ 50/60 Hz  Consumption - hot water  38.5 I  Consumption - cold water  77 I  Consumption - electric energy  5.168 kW/h  Consumption - cycle length  56 min  Control - Wavy  Yes  Electric water drain  3[2]  Chemical supply - soap hopper  Yes  Chemical supply - ready for liquid soap supply  Packaging dimensions  1065x1070x1610 mm	Motor - electronic control	Yes
Consumption - hot water 38.5 I  Consumption - warm water 77 I  Consumption - electric energy 5.168 kW/h  Consumption - cycle length 56 min  Control - Wavy Yes  Electric water drain 3   Chemical supply - soap hopper Yes  Chemical supply - ready for liquid soap supply Yes  Packaging dimensions 1065x1070x1610 mm	Motor - power	3.36 kW
Consumption - warm water 77 I  Consumption - cold water 77 I  Consumption - electric energy 5.168 kW/h  Consumption - cycle length 56 min  Control - Wavy Yes  Electric water drain 3   Chemical supply - soap hopper Yes  Chemical supply - ready for liquid soap supply Yes  Packaging dimensions 1065x1070x1610 mm	Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - cold water 77 I  Consumption - electric energy 5.168 kW/h  Consumption - cycle length 56 min  Control - Wavy Yes  Electric water drain 3 ?  Chemical supply - soap hopper Yes  Chemical supply - ready for liquid soap supply Yes  Packaging dimensions 1065x1070x1610 mm	Consumption - hot water	38.5 l
Consumption - electric energy  5.168 kW/h  Consumption - cycle length  56 min  Control - Wavy  Yes  Electric water drain  Chemical supply - soap hopper  Yes  Chemical supply - ready for liquid soap supply  Packaging dimensions  5.168 kW/h  Yes  1065x1070x1610 mm	Consumption - warm water	38.5 l
Consumption - cycle length  Control - Wavy  Yes  Electric water drain  Chemical supply - soap hopper  Chemical supply - ready for liquid soap supply  Packaging dimensions  56 min  Yes  Yes  1065x1070x1610 mm	Consumption - cold water	77 I
Control - Wavy Yes  Electric water drain 3 Chemical supply - soap hopper Yes  Chemical supply - ready for liquid soap supply Yes  Packaging dimensions 1065x1070x1610 mm	Consumption - electric energy	5.168 kW/h
Electric water drain 3[2] Chemical supply - soap hopper Yes Chemical supply - ready for liquid soap supply Yes Packaging dimensions 1065x1070x1610 mm	Consumption - cycle length	56 min
Chemical supply - soap hopper Yes Chemical supply - ready for liquid soap supply Yes Packaging dimensions 1065x1070x1610 mm	Control - Wavy	Yes
Chemical supply - ready for liquid soap supply  Yes  Packaging dimensions  1065x1070x1610 mm	Electric water drain	3[?]
Packaging dimensions 1065x1070x1610 mm	Chemical supply - soap hopper	Yes
	Chemical supply - ready for liquid soap supply	Yes
Gross weight 390 kg	Packaging dimensions	1065x1070x1610 mm
	Gross weight	390 kg