

HIGH SPIN WASHING MACHINE, 28 KG GWH 280E

Ref: 0903.12.039
Grandimpianti



Electronic control Wavy®: user interface adaptable to user needs and skills; unlimited possibility to create and customize programs. Possibility to record all working data.

Drum speed electronically managed (inverter), with control of drum rotation by sensor.

Redundant securities tested by certified laboratory.

Machine frame projected to fix the machine without moving it.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Patented weighing system to automatically weight the linen and regulate accordingly consumptions.

3 water inlets standard featured: hot, hard cold, soft cold, automatically managed and mixed by Wavy®.

Discharge pipe 3" with 90° bend and 3 water loading pipes 3/4" Standard featured (Hot water, cold water, soft water).

Self-Service program, as standard.

Optional: Payment system - Electromechanical coin meter, electronic coin meter and central payment system.

Ready for 13 liquid detergent inlets (optional), dispenser with 4 compartments ergonomically placed as standard.

Control card for 1 pump 24Vac or 24Vrac (A104).

Optional A103/A108 also controls the detergent consumption.

The data are related to the 60° C wash cycle reported on the standard ISO 9398

Capacity Load, min. - max. (1:10 / 1:9)	14 - 28 kg / 15.6 - 31.1 kg
Capacity drum	280 l - Ø 730x620 mm
Door	Ø 460 mm
Spin R.P.M	20 - 60 / 915
Spin G Factor	350
Noise	<65 dB
Dimensions (WDH)	970x1247x1460 mm
Weight net	475 kg
Weight gross	520 kg
Heating power - supplied with hot water only	Yes
Heating power - electric standard	22 kW
Motor - electronic control	Yes
Motor - power	4.6 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	61.3 l
Consumption - warm water	61.3 l
Consumption - cold water	122.4 l
Consumption - electric energy	7.847 kW/h
Consumption - cycle length	60 min
Control - Wavy	Yes
Electric water drain	3 ¹ / ₂
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes
Packaging dimensions	1100x1300x1600 mm
Gross weight	450 kg