



## REFRIGERATED COUNTER, 395 L GTRS-200 HC

Ref: 0161.462.003A Magnus

High quality austenitic stainless steel interior and exterior, except for galvanised back. Rounded corners inside and on the worktop. Injected polyurethane insulation with 40 kg/m3 density, free CFC. Ventilated cold. Electronic and digital control system of temperature and defrost. Doors with self-closing system and fixed opening. Automatic evaporation of defrosting water. Evaporator with epoxy anti-corrosion coating. Waste liquids are drained through the cleaning hole at the bottom of the cabinet. Height adjustable stainless steel feet.

Temperature range: -2 / +8 °C.

100 mm hygienic splashback.

R-290 Refrigerant.

Sliding group for easy cleaning and maintenance.

Includes 1 grid per door.

| FEATURES               |                  |
|------------------------|------------------|
| Dimensions (WDH)       | 2017x600x850 mm  |
| Power                  | 0.249 kW         |
| Cooling power          | 0.369 kW         |
| Power supply           | 230V/1/50Hz      |
| Capacity (gross / net) | 395 / 231 I      |
| Doors                  | 3                |
| Weight                 | 115 kg           |
| Energy class           | С                |
| Packaging dimensions   | 680x2150x1060 mm |
| Gross weight           | 125 kg           |