



GAS TUMBLE DRYER, 18 KG GDZ 450G

Ref: 0911.12.074 Grandimpianti

Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz $\!\!\!\! ^{\tiny \mbox{\scriptsize Miz}}\!\!\!\! ^{\tiny \mbox{\scriptsize B}}$: 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.

| FEATURES | |
|--------------------------------------|-----------------------|
| Capacity load (1:25); (1:20); (1:18) | 18 kg; 22.5 kg; 25 kg |
| Capacity drum | 450 I - Ø 940x640 mm |
| Door | Ø 612 mm |
| Drum rotation | 40 |
| Noise | < 55 dB |
| Dimensions (WDH) | 970x990x1810 mm |

| Weight net | 277 kg |
|------------------------------------|----------------------------|
| Weight gross | 292 kg |
| Control - G-WIZ | Yes |
| Drum/vacuum motor - Power | 1.1 kW |
| Power supply | 380 - 415 V 3 N ~ 50/60 Hz |
| Washing machines - ideal with | GWH180 |
| Heating power - Gas (double stage) | 16 - 24 kW |
| Consumption of evaporation | 14.21 l/h |
| Electric consumption | 0.5 kW/l |
| Natural gas G20 consumption | 2.6 m3/h |
| LPG gas G31 consumption | 1 kg/h |
| Packaging dimensions | 1100x1100x1850 mm |
| Gross weight | 291,5 kg |