



POT WASHER, RACK 550X550 MM AU-L 55.45 E PRS

Ref: 0810.35.011 Magnus

Stainless steel double-skinned body; stainless steel arms and injectors; preformed wash tank; preformed rack guides; automatic water supply; safety device on the door; rinsing with hot water through thermostop system; temperatures can be adjusted and checked electronically on the PC board; electronic controls; soft start: progressive start of the washing pump; automatic end-of-day self-cleaning cycle of washing tank; extractable control panel; integrated water suction group from the tank and drain for total drainage of the washing circuit (gravity drain); double water filtration; built-in electric rinse aid and detergent dispensers; anti-backflow valve.

PRS system (Atmospheric boiler+break tank)

2.5 I water consumption per cycle.

Cycles: 2 - 3 - 6 - 9 minutes.

Equipped with a 550x550 rack and a stainless steel rack for 4 trays.

| FEATURES | |
|------------------------|--|
| Dimensions (WDH) | 670x695x1315 mm |
| Production (baskets/h) | 30 - 15 - 10 - 7 (Depends on the cycle selected) |
| Tank capacity | 50 l |
| Boiler capacity | 5.5 |
| Working height | 450 (pots) / 410 (plates) mm |
| Total power | 6.75 kW |
| Tank and boiler power | 6/6 kW |
| Power supply | 400V/3/50 Hz |
| Washing pump | 0.75 kW |
| Weight | 97 kg |