

GAS TUMBLE DRYER, 24 KG GDZ 600G

Ref: 0911.12.076
 Grandimpianti



Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.

FEATURES

| | |
|--------------------------------------|-----------------------|
| Capacity load (1:25); (1:20); (1:18) | 24 kg; 30 kg; 33.3 kg |
| Capacity drum | 600 l - Ø 940x890 mm |
| Door | Ø 612 mm |
| Drum rotation | 40 |
| Noise | < 55 dB |
| Dimensions (WDH) | 970x1205x1810 mm |

| | |
|------------------------------------|----------------------------|
| Weight net | 296 kg |
| Weight gross | 311 kg |
| Control - G-WIZ | Yes |
| Drum/vacuum motor - Power | 1.1 kW |
| Power supply | 380 - 415 V 3 N ~ 50/60 Hz |
| Washing machines - ideal with | GWH240 |
| Heating power - Gas (double stage) | 16 - 24 kW |
| Consumption of evaporation | 20.6 l/h |
| Electric consumption | 0.5 kW/l |
| Natural gas G20 consumption | 2.6 m3/h |
| LPG gas G31 consumption | 1 kg/h |
| Gross weight | 311 kg |