



GAS TUMBLE DRYER, 24 KG GDZ 600G

Ref: 0911.12.076
Grandimpianti

Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.

FEATURES

Capacity load (1:25); (1:20); (1:18)	24 kg; 30 kg; 33.3 kg
Capacity drum	600 l - Ø 940x890 mm
Door	Ø 612 mm
Drum rotation	40
Noise	< 55 dB
Dimensions (WDH)	970x1205x1810 mm

Weight net	296 kg
Weight gross	311 kg
Control - G-WIZ	Yes
Drum/vacuum motor - Power	1.1 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Washing machines - ideal with	GWH240
Heating power - Gas (double stage)	16 - 24 kW
Consumption of evaporation	20.6 l/h
Electric consumption	0.5 kW/l
Natural gas G20 consumption	2.6 m3/h
LPG gas G31 consumption	1 kg/h
Gross weight	311 kg