



## GAS TUMBLE DRYER, 14 KG GDZ 350G

Ref: 0911.12.081 Grandimpianti

Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz  $\!\!\!\! ^{\tiny \mbox{\scriptsize Miz}}\!\!\!\! ^{\tiny \mbox{\scriptsize B}}$  : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.

FEATURES	
Capacity load (1:25); (1:20); (1:18)	14 kg; 17.5 kg; 19.5 kg
Capacity drum	350 I - Ø 740x800 mm
Door	Ø 612 mm
Drum rotation	40
Noise	< 55 dB
Dimensions (WDH)	795x1085x1590 mm

Weight net	215 kg
Weight gross	225 kg
Control - G-WIZ	Yes
Drum/vacuum motor - Power	0.75 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Washing machines - ideal with	GWH135
Heating power - Gas (double stage)	13 - 18 kW
	10 10 10 10 10 10 10 10 10 10 10 10 10 1
Consumption of evaporation	12 l/h
Consumption of evaporation  Electric consumption	
	12 l/h
Electric consumption	12 l/h 0.5 kW/l