

GAS TUMBLE DRYER, 14 KG GDZ 350G

Ref: 0911.12.081
 Grandimpianti



Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.

FEATURES

Capacity load (1:25); (1:20); (1:18) 14 kg; 17.5 kg; 19.5 kg

Capacity drum 350 l - Ø 740x800 mm

Door Ø 612 mm

Drum rotation 40

Noise < 55 dB

Dimensions (WDH) 795x1085x1590 mm

Weight net	215 kg
Weight gross	225 kg
Control - G-WIZ	Yes
Drum/vacuum motor - Power	0.75 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Washing machines - ideal with	GWH135
Heating power - Gas (double stage)	13 - 18 kW
Consumption of evaporation	12 l/h
Electric consumption	0.5 kW/l
Natural gas G20 consumption	1.9 m3/h
LPG gas G31 consumption	0.8 kg/h
Gross weight	225 kg