

RACK CONVEYOR DISHWASHER, RACK 500X500 MM - 1980 PLATES/H TR 1650

Ref: 0820.35.002A
Magnus



3 variable speed traction system by inverter.

Composed by an unique unit including wash and rinse.

Electromechanical controls.

Double skinned body and tank with rounded corners.

Double filtration de l'eau.

Stainless steel wash and rinse arms.

Self cleaning vertical pump.

Pressure reducer standard.

It allows the usage of GN1/1 trays with special rack.

Equipped with two racks for plates, one rack for cutlery, one base rack for cups and mugs and one cutlery basket with 8 divisions.

ESX version (model with left entry) / EDX version (models with right entry)

FEATURES

Dimensions (WDH)	1550x770x1710/2110 mm
Production (plates/h)	1980 - 1800 - 1620 (Depends on the cycle selected)
Production (glasses/h)	2750 - 2500 - 2250 (Depends on the cycle selected)
Production (trays/h)	660 - 600 - 540 (Depends on the cycle selected)
Production (racks/h)	110 - 100 - 90 (Depends on the cycle selected)
Working height	495 (plates) / 470 (glasses) mm
Total power	20.15 kW
Power supply	400V/3/50 Hz
Driving motor	0.15 kW
Washing	9 kW (tank) 2 kW (Washing pump)

	105l (tank)
Rising	9 kW (boiler)
	9l (boiler)
Water consumption	165 l/h
Gross weight	260 kg