



RACK CONVEYOR DISHWASHER, RACK 500X500 MM - 2880 PLATES/H TR 2500

Ref: 0820.35.009A Magnus

3 variable speed traction system by inverter.

Composed by an unique unit including wash and rinse.

Electromechanical controls.

Double skinned body and tank with rounded corners.

Double filtration de l?eau.

Stainless steel wash and rinse arms.

Self cleaning vertical pump.

Pressure reducer standard.

It allows the usage of GN1/1 trays with special rack.

Equipped with two racks for plates, one rack for cutlery, one base rack for cups and mugs and one cutlery basket with 8 divisions.

ESX version (model with left entry) / EDX version (models with right entry)

FEATURES	
Dimensions (WDH)	1800x770x1710/2110 mm
Production (plates/h)	2880 - 2520 - 1674 (Depends on the cycle selected)
Production (glasses/h)	4000 - 3500 - 2325 (Depends on the cycle selected)
Production (trays/h)	960 - 840 - 558 (Depends on the cycle selected)
Production (racks/h)	160 - 140 - 93 (Depends on the cycle selected)
Working height	495 (plates) / 470 (glasses) mm
Total power	29.6 kW
Power supply	400V/3/50 Hz
Driving motor	0.25 kW
Washing	12 kW (tank) 2.35 kW (Washing pump)

	105l (tank)
Rising	15 kW (boiler)
	2x 9l (boiler)
Water consumption	240 l/h
Gross weight	0,01 kg