

## HIGH SPIN WASHING MACHINE, 24 KG GWH 240E

Ref: 0903.12.036  
Grandimpianti

Electronic control Wavy®: user interface adaptable to user needs and skills; unlimited possibility to create and customize programs. Possibility to record all working data.

Drum speed electronically managed (inverter), with control of drum rotation by sensor.

Redundant securities tested by certified laboratory.

Machine frame projected to fix the machine without moving it.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached .

Patented weighing system to automatically weight the linen and regulate accordingly consumptions.

3 water inlets standard featured: hot, hard cold, soft cold, automatically managed and mixed by Wavy®.

Discharge pipe 3" with 90° bend and 3 water loading pipes 3/4" Standard featured (Hot water, cold water, soft water).

Self-Service program, as standard.

Optional: Payment system - Electromechanical coin meter, electronic coin meter and central payment system.

Ready for 13 liquid detergent inlets (optional), dispenser with 4 compartments ergonomically placed as standard.

Control card for 1 pump 24Vac or 24Vrac (A104).

Optional A103/A108 also controls the detergent consumption.

The data are related to the 60° C wash cycle reported on the standard ISO 9398



|  |                             |
|--|-----------------------------|
| Capacity Load, min. - max. (1:10 / 1:9)        | 12 - 24 kg / 13.4 - 26.7 kg |
| Capacity drum                                  | 240 l - Ø 730x540 mm        |
| Door   | Ø 460 mm                    |
| Spin R.P.M                                     | 20 - 60 / 970               |
| Spin G Factor                                  | 400                         |
| Noise  | <65 dB                      |
| Dimensions (WDH)                               | 970x1105x1460 mm            |
| Weight net                                     | 435 kg                      |
| Weight gross                                   | 455 kg                      |
| Heating power - supplied with hot water only   | Yes                         |
| Heating power - electric standard              | 18 kW                       |
| Motor - electronic control                     | Yes                         |
| Motor - power                                  | 4.6 kW                      |
| Power supply - standard                        | 380 - 415 V 3 N ~ 50/60 Hz  |
| Consumption - hot water                        | 51.4 l                      |
| Consumption - warm water                       | 51.4 l                      |
| Consumption - cold water                       | 102.5 l                     |
| Consumption - electric energy                  | 6.45 kW/h                   |
| Consumption - cycle length                     | 58 min                      |
| Control - Wavy                                 | Yes                         |
| Electric water drain                           | 3"                          |
| Chemical supply - soap hopper                  | Yes                         |
| Chemical supply - ready for liquid soap supply | Yes                         |
| Packaging dimensions                           | 1080x1100x1600 mm           |
| Gross weight                                   | 455 kg                      |