

ELECTRIC PIZZA OVEN WITH FULL REFRACTORY STONE CHAMBER, 2 CHAMBERS 670X685X150 MM - DIGITAL HDS44

Ref: 1040.775.019B
 Magnus



Possibility to prop a single oven on top of a double oven with the same chamber capacity, without the need for an exhauster connection or overlay kit/accessories (for example: HDS4 on top of HDS44).

Electric pizza oven was designed in order to combine high levels of performance and reliability with an innovative design.

It has a steel front, pre-painted body, steel door with glass, a knob for opening and closing the steam exhauster, non-thermal handles and an electronic card that is used to program the start, end of baking and two work settings (continuous/P2 and non-continuous/P1).

Double lighting low voltage (12V).

Refractory bricks with elements at sight on the top and refractory bricks with **ACTIVESTONE®** heating on the bottom.

FEATURES

Dimensions (WDH)	1090x1010x720 mm
Chamber dimensions (WDH)	2x 670x685x150 mm
Total power	13.2 kW
Upper power per chamber	4.2 kW
Lower power per chamber	2.4 kW
Power supply	400V/3/50Hz
Pizza capacity (Ø 34 cm)	4 + 4 un.
Temperature	450 °C
Weight	225 kg
Packaging dimensions	1100x1140x860 mm
Gross weight	220 kg