

ELECTRIC TUMBLE DRYER, 24 KG - THREE-PHASE GDZ 600E

Ref: 0911.12.075A
Grandimpianti

Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.



FEATURES

Capacity load (1:25); (1:20); (1:18)

24 kg; 30 kg; 33.3 kg

Capacity drum

600 l - Ø 940x890 mm

Door

Ø 612 mm

Drum rotation

40

Noise

< 55 dB

Dimensions (WDH)	970x1205x1810 mm
Weight net	296 kg
Weight gross	311 kg
Control - G-WIZ	Yes
Drum/vacuum motor - Power	1.1 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Washing machines - ideal with	GWH240
Heating power - Electric standard	15 + 15 kW
Consumption electric energy	17.4 kW/h
Consumption of evaporation	16.8 l/h
Packaging dimensions	1060x1400x1900 mm
Gross weight	311 kg