

ELECTRIC TUMBLE DRYER, 11 KG - THREE-PHASE GDZ 275E

Ref: 0911.12.077A
Grandimpianti

Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.



FEATURES

| | |
|--------------------------------------|-----------------------|
| Capacity load (1:25); (1:20); (1:18) | 11 kg; 14 kg; 15.3 kg |
| Capacity drum | 275 l - Ø 740x640 mm |
| Door | Ø 612 mm |
| Drum rotation | 40 |
| Noise | < 55 dB |

| | |
|-----------------------------------|----------------------------|
| Dimensions (WDH) | 795x920x1590 mm |
| Weight net | 205 kg |
| Weight gross | 215 kg |
| Control - G-WIZ | Yes |
| Drum/vacuum motor - Power | 0.75 kW |
| Power supply | 380 - 415 V 3 N ~ 50/60 Hz |
| Washing machines - ideal with | GWH105 |
| Heating power - Electric standard | 15 kW |
| Consumption electric energy | 7.35 kW/h |
| Consumption of evaporation | 7.67 l/h |
| Gross weight | 215 kg |