

## ELECTRIC TUMBLE DRYER, 14 KG - THREE-PHASE GDZ 350E

Ref: 0911.12.080A  
Grandimpianti

Optional drum inverter.

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.



### FEATURES

Capacity load (1:25); (1:20); (1:18)	14 kg; 17.5 kg; 19.5 kg
Capacity drum	350 l - Ø 740x800 mm
Door	Ø 612 mm
Drum rotation	40
Noise	< 55 dB

Dimensions (WDH)	795x1085x1590 mm
Weight net	215 kg
Weight gross	225 kg
Control - G-WIZ	Yes
Drum/vacuum motor - Power	0.75 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Washing machines - ideal with	GWH135
Heating power - Electric standard	18 kW
Consumption electric energy	9.75 kW/h
Consumption of evaporation	9.76 l/h
Packaging dimensions	1300x900x1690 mm
Gross weight	225 kg