



ASEPTIC WASHING MACHINE, 24 KG GA 24

Ref: 0920.12.007
Grandimpianti

Programmable control microprocessor.
Stainless steel body, tub and drum.
Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).
Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.
Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.
Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.
Available in steam version. Contact us!
The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

| | |
|--|----------------------------|
| Capacity Load, min. - max. (1:10 / 1:9) | 24 kg / 26.7 kg |
| Capacity drum | 240 l - Ø 750x544 mm |
| Doors per side | 1 |
| Pockets | 1 |
| Door | 496x325 mm |
| Spin R.P.M | 42 - 939 |
| Spin G Factor | 370 |
| Noise | <70 dB |
| Dimensions (WDH) | 1020x1145x1455 mm |
| Weight net | 460 kg |
| Weight gross | 515 kg |
| Heating power - supplied with hot water only | Opcional |
| Heating power - electric standard | 18 kW |
| Motor - electronic control | Yes |
| Motor - power | 3 kW |
| Power supply - standard | 380 - 415 V 3 N ~ 50/60 Hz |
| Consumption - hot water | 51.4 l |
| Consumption - warm water | 51.4 l |

| | |
|--|-------------------|
| Consumption - cold water | 102.7 l |
| Consumption - cycle length | 58 min |
| Control - PLC | Yes |
| Electric water drain | 1x 3 ² |
| Chemical supply - soap hopper | Yes |
| Chemical supply - ready for liquid soap supply | Yes |