

BAIN MARIE COUNTER WITHOUT STORAGE, 4X GN1/1, 150 MM SSBM-16

Ref: 1186.462.018
Magnus

Bain-marie indirect water heating with hidden silicon resistors attached to the bottom of the well. Silicon resistors improve heating performance and reduce electrical consumption.

Stamped well, with rounded edges for easy cleaning.

The regulation and control of the bain-marie temperature is carried out by means of an analogue thermometer and a thermostat.

Counters with heated storage, the storage temperature is controlled with a separate thermostat.

Operating pilot light.

Water inlet and drainage taps included.

Height-adjustable, robust feet.

External and internal structure made of AISI-304 18/10 stainless steel.

Glass foodshields and glass shelving can be assembled on top of the counter as optional.

The front panel can be coated with different colors.

Tray slide supplied disassembled from the counter. To be ordered separately as an option.

Containers not included.

Important note: Well must contain water when bain-marie is started.

The 16 models are ready to connect to 400V. However, it can be changed quickly and easily to 230V at the connection terminal.



SBM-311

FEATURES

Dimensions (WDH) 1600x700x850 mm

Power 2.1 kW

Power supply 400V/3/50 Hz

Capacity	4x GN1/1, 150 mm
Temperature	+30 °C / +90 °C
Type	Without storage