



BAIN-MARIE CENTRAL ISLAND-STYLE COUNTER, 4X GN1/1, 200 MM SSIBM-16

Ref: 1186.462.021 Magnus

Accessibility from both sides, being possible to assemble tray slides on the long sides of the counter.

Bain-marie indirect water heating with hidden silicon resistors attached to the bottom of the well. Silicon resistors improve heating performance and reduce electrical consumption.

Stamped well, with rounded edges for easy cleaning.

The regulation and control of the bain-marie temperature is carried out by means of a analogue thermometer and a thermostat.

Operating pilot light.

Water inlet and drainage taps included.

Height-adjustable, robust feet.

External and internal structure made of AISI-304 18/10 stainless steel.

As an option, a top with light or with light and heat can be installed.

The front panel can be coated with different colors.

Tray slide supplied disassembled from the counter. To be ordered separately as an option.

Containers not included.

Important note: Well must contain water when bain-marie is started.

Ready to connect to 400V. However, it can be changed quickly and easily to 230V at the connection terminal.

Power supply	230V/1/50Hz or 400V/3/50 Hz
Power	2.1 kW
Dimensions (WDH)	1600x700x850 mm
FEATURES	

Capacity	4x GN1/1, 150 mm
Temperature	+30 °C / +90 °C
Туре	With storage