

**ELECTRIC TUMBLE DRYER, 40 KG -
THREE-PHASE
GD 1000 E**

Ref: 0911.12.111
Grandimpanti

Electronic control Wavy®: user interface adaptable to user needs and skills; unlimited possibility to create and customize programs. Possibility to record all working data.



Unlimited programs, to manage manually and optimize consumptions. 10 already programmed. Times and temperatures automatically managed.

Reversing drum function to assure always a uniform drying action even with big linen.

Drum made of stainless steel AISI 430.

Outlet air filtered with double inox filter mesh.

The average energy consumption is of 1 kW/kg.

More efficiency in every operation ☐ save up to 12 minutes per cycle and achieve up to 4 extra cycles in an 8-hour shift.

Porthole at 830-840 mm from the floor to allow the direct approach with the trolley.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and frontal access to the lint filter system.

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

FEATURES

Capacity load (1:25); (1:20)	40 kg / 50 kg
Capacity drum	998 l
Door	Ø 612 mm
Drum rotation	28 - 43 r.p.m
Noise	< 65 db
Dimensions (WDH)	1140x1710x1950 mm
Weight net	485 kg

Weight gross	500 kg
Control - WAVY	Yes
Ideal with washing machine	GWH450
Electric power	54 kW
Electric power - Drum motor	1.1 kW
Electric power - Vacuum motor	1.1 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Evaporation capacity	42 l/h
Electric consumption	46 kWh
Cycle length	40 min.