

## AUTOMATIC ROLLER IRONER WITH ROLLER SPEED CONTROL + ARAMID ROLLER, Ø 180X1200 MM

### GI 1218 E VT ARAMIDIC

Ref: 0912.12.038  
Grandimpianti



Automatic basin movement through a patented maintenance-free and self-regulating system.

Aluminium basin treated with deep anodization to guarantee greater heat transmission, durability and energy savings.

Front loader use: The ironer can be installed against a wall.

Height adjustable wooden board and movable pedal to ensure the operator's maximum comfort.

Control panel positioned to be operated with just one finger.

Finger safety band protects the user in case of mishandling and power failure.

Safety thermostat avoids undesirable overheating, with manual reset.

FOX controller - 4 speeds, 4 temperatures, and 4 shell impulse.

VT = Roller speed control + thrust adjustment.

#### FEATURES

Dimensions (WDH)	1410x395x1070 mm
Total power	4.68 kW
Heating power	4.5 kW
Power supply	380 - 415 V 3 N ~ 50/60Hz
Capacity	29 kg/h (H.R. 10-15%)
Roller	Ø 180x1200 mm
Speed roller	1.3 - 3 m/min
External padding	Aramid
Movement by motor (basin)	Standard
Thrust adjustment (basin)	Yes
Heating surface	0.216 m2
Laundry introduction (Height from floor)	980 mm

Electronic control	FOX
Net weight	105 kg