

AUTOMATIC ROLLER IRONER WITH ROLLER SPEED CONTROL + ARAMID ROLLER, Ø 180X1200 MM

GI 1218 E VT ARAMIDIC

Ref: 0912.12.038
 Grandimpianti

Automatic basin movement through a patented maintenance-free and self-regulating system.

Aluminium basin treated with deep anodization to guarantee greater heat transmission, durability and energy savings.

Front loader use: The ironer can be installed against a wall.

Height adjustable wooden board and movable pedal to ensure the operator's maximum comfort.

Control panel positioned to be operated with just one finger.

Finger safety band protects the user in case of mishandling and power failure.

Safety thermostat avoids undesirable overheating, with manual reset.

FOX controller - 4 speeds, 4 temperatures, and 4 shell impulse.

VT = Roller speed control + thrust adjustment.



FEATURES

| | |
|--|---------------------------|
| Dimensions (WDH) | 1410x395x1070 mm |
| Total power | 4.68 kW |
| Heating power | 4.5 kW |
| Power supply | 380 - 415 V 3 N ~ 50/60Hz |
| Capacity | 29 kg/h (H.R. 10-15%) |
| Roller | Ø 180x1200 mm |
| Speed roller | 1.3 - 3 m/min |
| External padding | Aramid |
| Movement by motor (basin) | Standard |
| Thrust adjustment (basin) | Yes |
| Heating surface | 0.216 m ² |
| Laundry introduction (Height from floor) | 980 mm |

Electronic control

FOX

Net weight

105 kg