

## DISHWASHER, RACK 500X500 MM, THREE-PHASE AF 50.35 EL TR

Ref: 0805.35.062  
 Magnus



Stainless steel arms, injectors and body; partial double skinned body; double panel door; preformed wash tank; preformed rack guides; automatic water supply; rinsing with hot water through thermostop system; built-in electric rinse aid dispenser; door operated start/stop functions; automatic end-of-day self-cleaning cycle of washing tank; electronically adjustable tank and boiler temperatures; electronic controls; integrated water suction group from the tank and drain for total drainage of the washing circuit (gravity drain); anti-backflow valve.

LED display showing boiler temperature, tank temperature, and machine operating phases.

Electronic control with self-diagnostic system.

Green function: reduces energy waste when the machine is idle by maintaining the boiler temperature at 75°C.

2l water consumption per cycle.

Cycles: 1.5 - 2 - 3 - 9 minutes.

It allows the usage of GN1/1 trays with special rack.

Equipped with a rack for plates, a rack for glasses and a square base rack for cutlery .

Version with drain pump, ask us.

### FEATURES

Dimensions (WDH)	572x633x814 mm
Production (racks/h)	40 - 30 - 20 - 7 (Depends on the cycle selected)
Total power	5.05 kW
Power	2.4 kW (tank) / 4.5 kW (boiler) / 0.55 kW (Washing pump)
Power supply	400V/3/50 Hz
Boiler and tank capacity	20l (tank) / 5l (boiler)
Working height	365 (plates) / 340 (glasses) mm
Weight	55.5 kg