

DISHWASHER, RACK 400X400 MM AS 40.30 EPI PRS SD

Ref: 0805.35.067

Aristarco



Stainless steel double-skinned body; stainless steel arms, injectors; preformed wash tank; preformed rack guides; automatic water supply; rinsing with hot water through thermostop system; built-in electric rinse aid and detergent dispensers; door operated start/stop functions; automatic end-of-day self-cleaning cycle of washing tank; electronically adjustable tank and boiler temperatures; electronic controls; integrated water suction group from the tank and drain for total drainage of the washing circuit; anti-backflow valve.

LCD display showing boiler temperature, tank temperature, and machine operating phases.

Soft start: progressive start of the washing pump.

Electronic control with self-diagnostic system.

Green function: reduces energy waste when the machine is idle by maintaining the boiler temperature at 75°C.

2l water consumption per cycle.

PRS system (Atmospheric boiler+break tank).

SD System (Smart drain without overflow pipe).

Cycles: 1.5 - 2 - 3 - 9 minutes.

Equipped with two racks for glasses, a square base rack for cutlery and a rack for saucers.

Option to install a reverse osmosis system.

FEATURES

Dimensions (WDH)	483x550x700 mm
Production (racks/h)	40 - 30 - 20 - 7 (Depends on the cycle selected)
Total power	5.73 kW
Power	2.4 kW (tank) / 5.4 kW (boiler) / 0.33 kW (Washing pump)
Power supply	400V/3/50Hz
Boiler and tank capacity	12l (tank) / 4l (boiler)
Working height	315 (plates) / 290 (glasses) mm
Weight	49 kg