

DISHWASHER, RACK 500X600 MM AS 60.40 EPI PRS SD

Ref: 0805.35.069
Aristarco



Stainless steel double-skinned body; stainless steel arms and injectors; preformed wash tank; preformed rack guides; automatic water supply; rinsing with hot water through thermostop system; built-in electric rinse aid and detergent dispensers; soft start: progressive start of the washing pump ; door operated start/stop functions; automatic end-of-day self-cleaning cycle of washing tank; electronically adjustable tank and boiler temperatures; electronic controls; integrated water suction group from the tank and drain for total drainage of the washing circuit; anti-backflow valve.

LCD display showing boiler temperature, tank temperature, and machine operating phases.

Electronic control with self-diagnostic system.

Green function: reduces energy waste when the machine is idle by maintaining the boiler temperature at 75°C.

PRS system (Atmospheric boiler+break tank).

SD System (Smart drain without overflow pipe).

2l water consumption per cycle.

Cycles: 1.5 - 2 - 3 - 9 minutes.

It allows the usage of 60x40 cm trays with special rack (cod. 90805.35.733 or cod. 90805.35.875).

Equipped with a rack for plates, a rack for glasses and a square base rack for cutlery.

Option to install a reverse osmosis system.

FEATURES

Dimensions (WDH)	600x703x850 mm
Production (racks/h)	40 - 30 - 20 - 7 (Depends on the cycle selected)
Total power	6.68 kW
Power	2.4 kW (tank) / 6 kW (boiler) / 0.68 kW (Washing pump)
Power supply	400V/3/50 Hz
Boiler and tank capacity	22l (tank) / 5.5l (boiler)
Working height	410 (plates) / 380 (glasses) mm
Weight	73 kg