



ASEPTIC WASHING MACHINE, 33 KG UNI330

Ref: 0920.845.001 Magnus

UNI Smart Weigh automatically adjusts washing parameters to the actual load size (parameter to be specified by the operator), optimizing water, energy, and detergent use while maintaining excellent cleaning results.

Brake system with frequency inverter: braking is achieved via the motor through a frequency inverter, reducing mechanical brake usage, minimizing wear, and extending the lifespan of brake components.

Touch panel: customize up to 100 wash programs for various textile and hygiene needs (including 12 pre-set programs); delayed start option; multiple access levels (technicians, operators, etc); power cut detection (resumes the wash cycle from the interruption point after a power outage - no need to restart). Steam version available. Ask us!

Optionals

UNITANK (Water Recovery System): reuses water from previous cycles, saving up to 70% water, 40% energy, and 10% detergent. Constructed from stainless steel for durability and easy maintenance.

Network connectivity (connects to a local network for remote monitoring, updates and program control).

Automatic load weighing - Integrated load cells precisely measure laundry weight and automatically adjust water, detergent and energy usage. The system also maintains balanced drum loading for optimal performance.

| FEATURES | |
|--------------------------------------|--------------------|
| Capacity Load, min max. (1:10 / 1:9) | 33 kg / 37 kg |
| Capacity drum | 330 / Ø 775x700 mm |
| Pockets | 1 |
| Door | 650x340 mm |
| Spin | 915 rpm |
| Spin G Factor | 360 |
| Noise | < 80 dB |
| Dimensions (WDH) | 1730x1163x1685 mm |
| Net weight | 1500 kg |
| Gross weight | 1670 kg |
| | |