


BLAST CHILLER AND SHOCK FREEZER FOR 20 GN2/1 TROLLEY, WITH BUILT-IN GROUP FT20.80PI PURE

Ref: 0165.844.002 Sin Of Cold

* Depth with ramp ** Evap. -10°C / Cond. +45°C



Forced draught refrigeration with optimised air circulation.

Evaporator with cataphoresis treatment.

R452A refrigerant.

7? Touch screen.

Electronic and digital control system of temperatures and defrost.

80 mm of injected polyurethane insulation, free CFC.

AISI 304 Stainless steel interior and exterior.

Door with magnetic closure.

Depth with door at 90°: 2208 mm.

HACCP traceability system with alarm and temperature log, and the option of extracting data.

Alarm to avoid long time door openings.

Heated core probe.

Equipped with USB input as standard and ramp.

		=
		2
		COLD
	SIN	COLD

FEATURES	
Dimensions (WDH)	890x1375/1822*x2460 mm
Chamber dimensions (WDH)	700x850x1900 mm
Power	4.8 kW
Cooling power **	9.7 kW
Power supply	400V/3/50 Hz
Cooling (+65 to + 10°C) cycle 120 min.	80 kg

 Freezing (+65 to -18 °C) cycle 270 min.
 50 kg

 Weight
 350 kg