


BLAST CHILLER AND SHOCK FREEZER FOR 20X GN2/1 TROLLEY WITH AIR REMOTE UNIT (UP TO 10 M) FTW20.100 PURE

Ref: 0165.844.003 Sin Of Cold

* Depth with ramp ** Evap. -10°C / Cond. +45°C



Forced draught refrigeration with optimised air circulation.

Evaporator with cataphoresis treatment.

R452A refrigerant.

7? Touch screen.

Electronic and digital control system of temperatures and defrost.

80 mm of injected polyurethane insulation, free CFC.

AISI 304 Stainless steel interior and exterior.

Ergonomic handle and magnetic closure.

Depth with door at 90°: 2130 mm.

HACCP traceability system with alarm and temperature log, and the option of extracting data.

Alarm to avoid long time door openings.

Heated core probe.

Remote unit with air condensation.

Equipped with USB input as standard and ramp.



FEATURES	
Dimensions (WDH)	1250x1355/1845*x2260 mm
Chamber dimensions (WDH)	790x1020x1895 mm
Power	5 kW
Cooling power **	12 kW

Power supply	400V/3/50 Hz
Cooling (+65 to + 10°C) cycle 120 min.	100 kg
Freezing (+65 to -18°C) cycle 270 min.	60 kg
Weight	280 kg (un.) + 210 kg (remote unit)