



## GLASSWASHER WITH DRAIN PUMP, RACK 400X400 MM AF 40.30 EL

Ref: 0800.35.018A Magnus

Stainless steel arms, injectors and body; partial double skinned body; double panel door; preformed wash tank; preformed rack guides; automatic water supply; rinsing with hot water through thermostop system; built-in electric rinse aid dispenser; door operated start/stop functions; automatic end-of-day self-cleaning cycle of washing tank; electronically adjustable tank and boiler temperatures; electronic controls; integrated water suction group from the tank and drain for total drainage of the washing circuit (drain pump); anti-backflow valve.

LED display showing boiler temperature, tank temperature, and machine operating phases.

Electronic control with self-diagnostic system.

Green function: reduces energy waste when the machine is idle by maintaining the boiler temperature at 70?°C.

21 water consumption per cycle.

Cycles: 1.5 - 2 - 3 - 9 minutes.

Equipped with two racks for glasses, a square base rack for cutlery and a rack for saucers.

FEATURES	
Dimensions (WDH)	455x550x700 mm
Production (racks/h)	40 - 30 - 20 - 7
Total power	2.89 kW
Power	2.4 kW (tank) / 2.7 kW (boiler) / 0.19 kW (Washing pump)
Power supply	230V/1/50 Hz
Boiler and tank capacity	12I (tank) / 3I (boiler)
Working height	300 mm
Weight	36.5 kg