

POT WASHER, RACK 1260X815 MM EU 125.80 EPI PRS

Ref: 0810.35.023A
 Magnus



Stainless steel double-skinned body, insulated body; stainless steel arms and injectors; preformed wash tank; automatic water supply; rinsing with hot water through thermostop system; built-in electric rinse aid and detergent dispensers; electronically adjustable tank and boiler temperatures; electronic controls; double water filtration; direct filling into tank; self clearing vertical pump; automatic end-of-day self-cleaning cycle of washing tank; hose for the total emptying of the boiler; insulated tank and boiler to reduce heat dispersion; anti-backflow valve.

PRS system (Atmospheric boiler+break tank).

LCD display showing boiler temperature, tank temperature, and machine operating phases.

Electronic control with self-diagnostic system.

Green function: reduces energy waste when the machine is idle by maintaining the boiler temperature at 75°C.

7 l water consumption per cycle.

Cycles: 2 - 3 - 6 - 9 minutes.

Equipped with stainless steel rack.

FEATURES

| | |
|------------------------|--|
| Dimensions (WDH) | 1436x995x2034/2330 mm |
| Production (baskets/h) | 30 - 20 - 10 - 7 (Depends on the cycle selected) |
| Tank capacity | 100 l |
| Boiler capacity | 17 l |
| Working height | 800 mm |
| Total power | 15 kW |
| Tank power | 9 kW |
| Boiler power | 9 kW |
| Washing pump | 2x 3 kW |
| Power supply | 400V/3/50 Hz |
| Weight | 314 kg |