

STEAM TUMBLE DRYER, 15 KG - THREE-PHASE EBV 15

Ref: 0911.12.033
Grandimpianti



Automatic inversion of the drum rotation with one inversion per minute.

Stainless steel drum and plasticized sheet-steel structure (Skin plate).

Air recycling system enables remarkable energy recovery.

Wide opening facilitates laundry loading.

Easy to open inspectable lint filter, made by stainless steel net.

Filter condition (% of dirtiness detected) showed on display.

Overload control; soft start (only EB 10 and EB 15 models); direct transmission instead of chain transmission; overcurrent protection switch on the motor.

Second temperature probe (only EB 41 model).

Every cycle is completed by an automatically controlled cooling stroke (permanent press), for an easy remover of the linen.

Optional: Payment system - Electromechanical coin meter, electronic coin meter and central payment system (only EB 10 and EB 15 models).

FEATURES

| | |
|------------------------------|----------------------|
| Capacity load (1:25); (1:20) | 12 kg; 15 kg |
| Capacity drum | 300 l - Ø 761x660 mm |
| Door | Ø 612 mm |
| Drum rotation | 20 - 80 |
| Noise | < 64 dB |
| Dimensions (WDH) | 795x970x1290 mm |
| Weight net | 134 kg |
| Weight gross | 153 kg |
| Control - G400 DRY | Yes |
| Drum motor - Power | 0.5 kW |

| | |
|----------------------------|----------------------------|
| Power supply | 380 - 415 V 3 N ~ 50/60 Hz |
| Consumption evaporation | 5 - 7 l/h |
| Consumption steam | 30 kg/h |
| Consumption steam pressure | 400/600 kPA - 4/6 bar |