



## PASTEURIZER, 60 L/CYCLE - WATER EVOPASTO 60

Ref: 0305.86.030

Telme

Water condensation.

Adequate for low and high pasteurization.

Heating temperature between + 60 and + 90 °C and cooling between 0 and + 20 °C.

All components in touch with the products are easily removable for cleaning.

2 Speeds 1400 rpm (production) and 700 rpm (conservation).

For larger productions, ask-us!

### FEATURES

|                  |                 |
|------------------|-----------------|
| Dimensions (WDH) | 420x780x1100 mm |
|------------------|-----------------|

|       |        |
|-------|--------|
| Power | 7.6 kW |
|-------|--------|

|              |             |
|--------------|-------------|
| Power supply | 400V/3/50Hz |
|--------------|-------------|

|                  |                 |
|------------------|-----------------|
| Mix for cylinder | 30 - 60 l/cycle |
|------------------|-----------------|

|               |                |
|---------------|----------------|
| Working cycle | 100 - 120 min. |
|---------------|----------------|

|        |        |
|--------|--------|
| Weight | 164 kg |
|--------|--------|

|                      |                  |
|----------------------|------------------|
| Packaging dimensions | 1035x535x1590 mm |
|----------------------|------------------|

|              |        |
|--------------|--------|
| Gross weight | 184 kg |
|--------------|--------|