



STAINLESS STEEL POTATO PEELER 10 KG, SINGLE-PHASE PI-10 MN

Ref: 0703.10.027 Sammic

Structure made of stainless steel.

Lateral stirrers covered with silicon carbide abrasives (approved by NSF).

Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purpose. Auto-drag of waste to the drain.

Energy efficiency thanks to engine optimization.

Liftable transparent polycarbonate cover, complete with locking and safety device.

Aluminium door with hermetic seal and safety device.

Control board with IP65 protection. Improved reliability against humidity and water splash.

Water inlet with non-return system.

PI-30: Water inlet system fitted with electric valve.

Auxiliary contact for external electric valve.

Timer 0-6 minutes and continuous operation.

Support not included.

Dimensions (WDH) 435x635x668 mm Dimensions with Stand (WDH) 433x638x1040 mm Power 0.55 kW Power supply 230V/1/50 Hz Maximum production 240 kg/h	
Power 0.55 kW Power supply 230V/1/50 Hz	
Power supply 230V/1/50 Hz	
Maximum production 240 kg/h	
Waxiinum production 240 kg/m	
Capacity per load 10 kg per cycle	
Weight 36 kg	
Packaging dimensions 460x650x800 mm	
Gross weight 44 kg	