



GN2/1 COMBI CABINET, 298 + 298 L GARCG-702 HC

Ref: 0116.462.002A
 Magnus

High quality austenitic stainless steel interior and exterior, except for galvanised back. Rounded outside and inside corners. 50 mm of injected polyurethane insulation with 40 kg/m³ density, free CFC. Ventilated refrigeration; R-290 refrigerant. electronic and digital control system of temperature and defrost. Doors with self-closing system. Alarm to avoid long time openings. Automatic defrosting. Automatic evaporation of defrosting water. Evaporator with epoxy anti-corrosion coating. waste liquids are drained through the cleaning hole at the bottom of the cabinet. Height adjustable stainless steel feet.

FEATURES

| | |
|----------------------------|------------------------|
| Dimensions (WDH) | 693x826x2008 mm |
| Temperature | -2 / +8 ; -22 / -15 °C |
| Chamber volume (gross/net) | 298+298 l / 218+218 l |
| Power | 867 W |
| Cooling power | 250 W |
| Power supply | 230V/1/50Hz |
| Weight | 146 kg |
| R-290 Refrigerant | 98 g |
| Doors | 2 |
| GN2/1 Grids | 1 |
| PVC containers | 3 |
| Energy class | D |
| Packaging dimensions | 860x730x2027 mm |
| Gross weight | 146 kg |